



PROFESSIONAL
CAPTIVE PORTAL AND
WIFI NETWORK AUDIT







PROFESSIONAL CAPTIVE PORTAL AND WIFI NETWORK AUDIT

The professional Ekselans by ITS HotSpot has been designed for installation in business and hotel environments, as well as in any public WiFi network where user authentication and activity registration are required.

Through a simple configuration, the installer is able to define all the necessary parameters to offer various methods of accreditation in WiFi networks (direct registration, email with verification check, tickets with pre-defined passwords, social networks, ...). Likewise, the system allows to define user profiles for assignment of times and connection speed.

In addition to the captive portal, the HotSpot by EK offers a powerful network audit system that allows analyzing internet consumption statistics by connection and user, as well as registering and storing the activity of the different users connected to the WiFi network (device identification, visited domains, connection times, ...), all in strict compliance with the new regulation

Captive portal

- Simple configuration of the welcome page
- Various access systems: direct registration, tickets with personalized passwords, social networks (Facebook)
- Possibility of defining fields for the access form (name, nationality, room, email, ...)
- Access functionality with email verification system
- Definition of bandwidth and maximum connection time per session
- Creation of websites whitelists
- Possibility of connection to ticket printer for passwords

Network audit and activity registration

- Activity log of users connected to the WiFi network
- Internal storage of important information such as devices MAC addresses, visited domains, connection times to each domain
- Usage statistics of internet resources per user
- Possibility of defining an external cloud back-up (Dropbox, Google Drive, ...)












REFERENCE	см нѕ
Code	280024
Hardware	
Ethernet interface	Uplink 1 x 10 / 100 / 1000 Mbps RJ45 LAN 1 x 10 / 100 / 1000 Mbps RJ45
HDMI interface	1 x HDMI 1080p
USB interface	1 x USB 2.0
Storage capacity	120 GB SSD
Power supply	DC 5V / 2.5A
Compatible power supplies	FA 55 (082010). Plug-in power supply. FA 524 (082009). Modular power supply compatible with EKOAX and CM Headend
General	
Working temperature	-20°C / 45°C
Dimensions	55 mm x 220 mm x 116 mm
Consumption	Max. 12 W
Software	
Programming	Web interface
Assign users and access	- Tickets - Login and password - Direct register - Social networks
Bandwidth limitation	Yes
Creation of different type of users	Customer profiles
DHCP server	Yes
System capacity	More than 400 simultaneous users / No limit of registered users
Activity log	Full audit and registration per user of: -Device MAC address -User name -Assigned IP -Visited domains -Start and end time of each domain visited
Statistics	Activity log / network consumption per user




INSTALLATION EXAMPLE




EXAMPLE 1


HotSpot by EK installation with EKOAX system (internet over coax)






1. Example of the welcome page (Captive portal)








2. HotSpot manager. Captive portal internal configuration page




3. HotSpot manager. Creation of user profiles






4. Cautive portal. Users management




5. Network audit. Statistical analysis of network consumption






6. Network audit. Statistical analysis of network consumption filtered by user.




7. Network audit. Users activity log register.





8. Network audit. Access to the log activity files.





ITS Partner O.B.S. S.L
Av. Corts Catalanes 9-11
08173 Sant Cugat del Vallès
Barcelona (Spain)
Tel: +34 935839543
info@ekselansbyits.com
www.ekselansbyits.com