

NOW AVAILABLE COAXIAL AND LAN CABLES WITH CPR DCA JACKET

Coaxial cables:

CC 96D (151025)

- ✓ Coaxial cable 6,8mm diameter. 96 wires.
- ✓ 1.0mm CU inner conductor.
- ✓ 85dB / Class A shielding.
- ✓ Attenuation: 17,9dB (862MHz) / 29,6dB (2150MHz).
- ✓ White PVC jacket.
- ✓ CPR Dca.
- ✓ Cardboard coil 100 m



CC 96+D (151026)

- ✓ Coaxial cable 6,8mm diameter. 96 wires.
- ✓ 1.13mm CU conductor.
- ✓ 85dB / Class A shielding.
- ✓ Attenuation: 17,4dB (862MHz) / 28,4dB (2150MHz).
- ✓ White PVC jacket.
- ✓ CPR Dca.
- ✓ Cardboard coil 100 m



CC 96+D 250 (151027)

- ✓ Coaxial cable 6,8mm diameter. 96 wires.
- ✓ 1.13mm CU conductor.
- ✓ 85dB / Class A shielding.
- ✓ Attenuation: 17,4dB (862MHz) / 28,4dB (2150MHz).
- ✓ White PVC jacket.
- ✓ CPR Dca.
- ✓ 250m cardboard coil (pull-box)



CC 112P-D (151028)

- ✓ Coaxial cable 6,6mm diameter. 112 wires.
- ✓ CCS 1.0mm inner conductor.
- ✓ 90dB / Class A shielding.
- ✓ Attenuation: 17,9dB (862MHz) / 29,6dB (2150MHz).
- ✓ Foil glued onto the dielectric.
- ✓ White PVC jacket.
- ✓ CPR Dca.
- ✓ Cardboard coil 100 m



CLU 6 CUD (390010)

- ✓ U / UTP LAN cable
- ✓ Cat-6 Dca CU
- ✓ LSZH White jacket CPR Dca
- ✓ Pull box 305m



93 583 95 43

info@ek.plus