

SCART DVB-T/T2 H265 RECEIVER

EK SS T2



EK SS T2

REFERENCE	EK SS T2
Code	180009
Main system	
CPU speed	600 MHz
Flash memory	32M bit
DDR3	512M bit
Tuner and demodulator	
ANT. Connector	IEC TYPE, female
Loop output	IEC TYPE, male
Frequency range input	50.5--858MHz
Input impedance	75 Ω
Input signal level	-82 dBm to -20 dBm (average power)
AUDIO/VIDEO DATA IN/OUT	
AV output:	Scart
HDMI	HDMI output
Operating environment	
Operating temperature	+0° - 70°
Storage temperature	-40° - +65°
MPEG AUDIO/ VIDEO DECODING	
Video	MPEG-2 (ISO/IEC 13818-2) MPEG-4 (ISO/IEC14496-2) H.264 (ISO/IEC14496-10) H.265 HEVC (Max 10bit)
Profile level	MPEG-2 MP@HL / MPEG-4 ASP@L5 HD / H.264HP@L4.1 * HEVC (max 10 bit) main profile @level 4.1,main profile 10@level 4.1
Entry fee	Max. 60M bits
Aspect ratio	4:3, 16:9, Auto
Video resolution	1920*1080i; 1280*720p; 720*576i
Audio decoding	MPEG-1 Layer I/II, MPEG-2 layer I/II, AAC, AAC+/HE-AAC/AC3,Dolby plus
Audio mode	Mono / Izquierda / Derecha / Estéreo
Sampling frequency	32, 44.1 & 48 KHz
Feeding	
Input voltage	AC100--240V, 50/60Hz Or 12V/1A
Type	AC/ DC Power



Display with integrated IR.
Displays channel (ON) and time (OFF)